Revision Date 10.04.2017 Revision: 1

1 Identification of the substance/mixture and the company/undertaking

1.1 Product identifier Trade name: WRC Resin

1.2 Application of the substance / the mixture: Wear resistant epoxy

1.3 Details of the supplier of the Safety Data Sheet

Manufacturer/Supplier:



Silicon Carbide Products, Inc.

361 Daniel Zenker Drive Horseheads, NY 14845 Phone: (607) 562-8599

1.4 Emergency telephone number:

ChemTel Inc.

(800) 255-3924, +1 (813) 248-0585

2 Hazards identification

2.1 GHS Classification of the substance or mixture

Skin Irritant 2; H315: Causes skin irritation. Eye Irritant 2; H319: Causes serious eye irritation. Skin Sensitizer 1; H317: May cause and allergic skin reaction.

2.2 GHS Label elements

Hazard pictograms/symbols



Signal word: Warning

Hazard statements:

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H317: May cause and allergic skin reaction.

Precautionary statements:

P280: wear protective gloves / eye protection.

P273: Avoid release to the environment. P264: Wash thoroughly after handling.

P261: Avoid breathing mist/vapours/spray.
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do .Continue rinsing.

P333+P313: If skin irritation or rash occurs: Get medical advice/attention.

P337+P313: If eye irritation persists: Get medical advice/attention.

Additional information: Contains epoxy constituents. May produce an allergic reaction.

HMIS Rating:

Health: Flammability: Physical Hazard:

Revision Date 10.04.2017 Revision: 1

3 Composition/information on ingredients

3.2 Mixture

Description: Substance listed below with nonhazardous additions possible.

Dangerous components:	·	
CAS: 25068-38-6	Reaction product: bisphenol - A- (epichlorohydrin) epoxy resin (number average molecular weight<700)	15-35%
Trade Secret	Diglycidyl ether	<10%

In conformity with 29CFR 1910.1200(i) the specific chemical identity may be withheld as Trade Secret, while all health/safety properties and effects are included in the SDS.

4 First aid measures

4.1 Description of first aid measures

General information: Immediately remove any clothing soiled by the product. Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident. Take affected persons out into the fresh air.

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact: Immediately rinse with water. If skin irritation continues, consult a doctor.

After eye contact: Remove contact lenses if worn, if possible. Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing: Rinse out mouth and then drink plenty of water. Do not Induce vomiting; call for medical help immediately. **4.2 Most important symptoms and effects, both acute and delayed:** Allergic reactions, Nausea, Coughing, Gastric or intestinal disorders. Irritant to skin and mucous membranes. Irritant to eyes.

4.3 Indication of any immediate medical attention and special treatment needed: Contains reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700), Reaction May produce an allergic reaction. If necessary oxygen respiration treatment. Later observation for pneumonia and pulmonary edema. Medical supervision for at least 48 hours.

5 Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents: Water haze or fog, Foam, Fire-extinguishing powder, Carbon dioxide.

For safety reasons unsuitable extinguishing agents: Water with full jet, Water spray

5.2 Special hazards arising from the substance or mixture:

Formation of toxic gases is possible during heating or in case of fire.

5.3 Advice for the firefighters

Protective equipment: Wear self-contained respiratory protective device, Wear fully protective suit.

Additional information: Cool endangered receptacles with water fog or haze. Eliminate all ignition sources if safe to do so.

6 Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures:** Use respiratory protective device against the effects of fumes/dust/aerosol. Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation. Keep away from ignition sources.
- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water. Inform respective authorities in case of seepage into water course or sewage system. Prevent from spreading (e.g. by damming–in or oil barriers).
 6.3 Methods and material for containment and cleaning up: Absorb liquid components with liquid-binding material.
 Send for recovery or disposal in suitable receptacles. Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.

7 Handling and storage

- **7.1 Precautions for safe handling:** Use only in well-ventilated areas. Store in cool, dry place in tightly closed receptacles. (60-80F recommended)
- **7.2 Conditions for safe storage, including any incompatibilities:** Use only receptacles specifically permitted for this substance/product. Avoid storage near extreme heat, ignition sources or open flame.

Further Information about storage conditions: Keep container tightly sealed. Store in an area with adequate ventilation.

Revision Date 10.04.2017 Revision: 1

8 Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace: The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

DNELs: No further relevant information available. **PNECs:** No further relevant information available.

Additional information: The lists valid during the making were used as basis.

8.2 Engineering controls Provide readily accessible eye wash stations and safety showers. Provide ventilation adequate to ensure concentrations are minimized.

8.3 Personal protective equipment

General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Do not inhale gases / fumes / aerosols. Avoid contact with the eyes and skin.

Respiratory protection: Not required under normal conditions of use. Use suitable respiratory protective device in case of insufficient ventilation. For spills, respiratory protection may be advisable. Use respiratory protection when grinding or cutting material.

Hand protection: Protective, impervious gloves. (Neoprene, PVC, Nitrile rubber) The glove material has to be impermeable and resistant to the product / the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation.

Eye protection: Safety glasses with side shields. Contact lenses should not be worn.

Skin and Body protection: Protective work clothing. Where potential exposure warrants, rubber or plastic boots and chemically resistant protective suit.

9 Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Appearance Form:

Form: Paste Colour: Black Odour: Sweet

Odour threshold: No data available No data available Melting point/range: No data available >392 °F / >200 °C Boiling point/range: Flash point: >302 °F / >150 °C **Evaporation rate:** No data available Flammability (solid, gaseous): Not applicable Upper/lower flammability or explosive limit: Not applicable Vapor pressure: No data available Vapor density: No data available Relative Density at 20°C: 2.20 a/cm3

Solubility in / Miscibility with

Water: Not miscible or difficult to mix.

Partition coefficient (n-octanol/water):

Auto/Self-ignition temperature:

No data available

No data available

No data available

Viscosity Paste

10 Stability and reactivity

10.1 Reactivity

10.2 Chemical stability

Thermal decomposition / conditions to be avoided: No decomposition if used and stored according to specifications.

10.3 Possibility of hazardous reactions: Reacts with strong alkali. Exothermic polymerization. Reacts with strong acids and oxidizing agents. Reacts with catalysts.

10.4 Conditions to avoid: Avoid contact with strong oxidizing agents, excessive heat or flames.

10.5 Incompatible materials: Strong acids, bases and oxidizing agents.

10.6 Hazardous decomposition products: Carbon monoxide and carbon dioxide.

Revision Date 10.04.2017 Revision: 1

11 Toxicological information

11.1 Information on likely routes of exposure:

Inhalation: May cause respiratory irritation

Indestion: No data

Skin contact: May cause skin irritation
Eye contact: May cause eye irritation

11.2 Symptoms related to physical, chemical and toxicological characteristics: No available data 11.3 Delayed and immediate effects as well as chronic effects from short and long-term exposure:

(Data for primary component, Reaction product: bisphenol - A- (epichlorhydrin) epoxy resin)

Acute toxic:

Oral LD50 > 2,000 mg/kg (rat) Dermal LD50 > 2,000 mg/kg (rat)

Inhalation No data

Skin Corrosive/irritant:

Test material was slightly irritating to skin in key studies. For the skin, mean erythema and edema scores were

0.8 and 0.5 respectively. Serious eye damage/eye irritation:

Test material was slightly irritating to the eye in key studies. The mean eye score was 0.4

Respiratory sensitization: No data available

Skin sensitization:

In a local lymph node assay, the concentration that would cause a 3-fold increase in proliferation (EC-3) was calculated to be 5.7% which is consistent with moderate dermal sensitization potential.

11.4 Numerical measures of toxicity: No data available for mixture.

Additional toxicological information: The product show the following dangers according to the calculation method of the General EU, Classification Guidelines for Preparations as issued in the latest version: Irritant, Danger through skin absorption. Toxic and /or corrosive effects may be delayed up to 24 hours. Inhalation of concentrated vapours as well as oral intake will lead to anesthesia-like conditions and headache, dizziness .etc.

12 Ecological information

12.1 Toxicity

Aquatic toxicity:

(Data taken from SDS of primary component, Reaction product: bisphenol - A- (epichlorhydrin) epoxy resin)

Fish 96hr-LC50 = 3.6mg/L test mat. *Oncorhynchus mykiss*

(direct application, nominal) (OECD Guideline 203)

LC50 1.41 mg/L 96hr Oryzias latipes

Crustacea 48hr-EC50 = 2.8mg/L test mat Daphnia magna

(direct application, nominal, based on: mobility) (OECD Guideline 202)

EC50 1.7mg/L 48hr

Aquatic Plant 72hr-EC50 > 11 mg/L Scenedesmus capricornutum

water soluble fraction (meas. (arithm. mean)) based on: growth rate (EPA-660/3-75-009)

12.2 Persistence and degradability: No data available.

12.3 Bioaccumulative potential: No further relevant information available.

12.4 Mobility in soil: No further relevant information available.

12.5 Results of PBT and vPvB assessment:

PBT: Not applicable. **vPvB:** Not applicable.

12.6 Other adverse effects: No further relevant information available

13 Disposal considerations

13.1 Waste treatment methods

Waste from residue/unused product: This product should not be allowed to enter drains, water courses or the soil.

Dispose of this material in a safe manner and in accordance with federal, state and local regulations

Contaminated packaging: Disposal must be made in accordance with official federal, state and local regulations.

Revision Date 10.04.2017 Revision: 1

14 Transport information

DOT

UN number: Not Regulated

IATA

UN number: Not Regulated

IMDG

UN number: Not Regulated

TDG

UN number: Not Regulated

15 Regulatory Information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

United States (USA)

SARA

VAINA
Section 355 (extremely hazardous substances):
None of the ingredients is listed.
Section 313 (Specific toxic chemical listings):
Component(s) above 'de minimus' level: None
TSCA (Toxic Substances Control Act):
All the ingredients are listed.

Proposition 65 (California):

Chemicals known to cause cancer or reproductive toxicity: Ethylene glycol

Canada

(Ca	ına	ıdiar	ı Do	mest	ic S	ubst	ances	List	(DSL):	
	ΛТ	1:				1:-4-	_				

All ingredients are listed.

Canadian Ingredient Disclosure list (limit 0.1%)

None of the ingredients is listed.

Canadian Ingredient Disclosure list (limit 1%)

None of the ingredients is listed.

15.2 Chemical Safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Abbreviation and acronyms:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association GHS: Globally Harmonized System of Classification and Labelling of Chemicals

ACGIH: American Conference of Governmental Industrial Hygienist.

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substance

CAS: Chemical Abstracts Service (division of the American Chemical Society)

HMIS: Hazardous Materials Identification System (USA)

WHMIS: Workplace Hazardous Materials Information System (Canada)

Revision Date 10.04.2017 Revision: 1

Revision Date 10.04.2017 Revision: 1

1 Identification of the substance/mixture and the company/undertaking

1.1 Product identifier Trade name: WRC Hardener

1.2 Application of the substance / the mixture: Wear resistant epoxy

1.3 Details of the supplier of the Safety Data Sheet

Manufacturer/Supplier:



Silicon Carbide Products, Inc.

361 Daniel Zenker Drive Horseheads, NY 14845 Phone: (607) 562-8599

1.4 Emergency telephone number:

ChemTel Inc.

(800) 255-3924, +1 (813) 248-0585

2 Hazards identification

2.1 GHS Classification of the substance or mixture

Acute toxicity - Oral Category 4
Skin corrosion - Category 1B
Serious Eye Damage - Category 1
Skin sensitization - Category 1
Reproductive toxicity - Category 2

Specific target organ toxicity - repeated exposure - Oral Category 2

2.2 GHS Label elements

Hazard pictograms/symbols



Signal word: Danger

Hazard statements:

H302: Harmful if swallowed.

H314: Causes severe skin burns and eye damage.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H335: May cause respiratory irritation.

H361: Suspected of damaging fertility or the unborn child

H373a: May cause damage to organs through prolonged or repeated exposure if swallowed.

Precautionary statements:

P202: Do not handle until all safety precautions have been read and understood.

P261: Avoid breathing dust/fume/gas/mist/vapours/spray.

P264: Wash hands thoroughly after handling.

P270: Do not eat, drink or smoke when using this product.

P272: Contaminated work clothing should not be allowed out of the workplace.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P281: Use personal protective equipment as required P201: Obtain special instructions before use.

P301+P312: IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

P301+P330+P331: IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

P303+P361+P353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313: IF exposed or concerned: Get medical advice/attention.

P310: Immediately call a POISON CENTRE or doctor/physician.

Revision Date 10.04.2017 Revision: 1

P333+P313: If skin irritation or rash occurs: Get medical advice/attention.

P363: Wash contaminated clothing before reuse.

Additional information: Harmful if swallowed, May cause sensitization by skin contact, Corrosive

HMIS Rating:

Health: 3 Flammability: 1 Physical Hazard: 0

3 Composition/information on ingredients

3.2 Mixture

Description: Mixture of substances listed below with potential nonhazardous additions.

Dangerous componer	nts:	
CAS: 98-54-4	Paratertiarybutylphenol	5-15%
Trade Secret	Polyamidoamine	5-10%
Trade Secret	Aliphatic amine	<10%
CAS: 2579-20-6	1,3-Cyclohexanedimethanamine	<10%

In conformity with 29CFR 1910.1200(i) the specific chemical identity may be withheld as Trade Secret, while all health/safety properties and effects are included in the SDS.

4 First aid measures

4.1 Description of first aid measures

General information: Seek medical advice. If breathing has stopped or is labored, give assisted respirations. Supplemental oxygen may be indicated. If the heart has stopped, trained personnel should begin cardiopulmonary resuscitation immediately

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact: Immediately remove contaminated clothing, and any extraneous chemical, if possible to do so without delay. Take off contaminated clothing and shoes immediately.

After eye contact: Rinse immediately with plenty of water for at least 15 minutes. If symptoms persist, consult a doctor. **After ingestion:** Never give anything by mouth to an unconscious person. Prevent aspiration of vomit. Turn victim's head to the side. Do not Induce vomiting; call for medical help immediately.

- **4.2 Most important symptoms and effects, both acute and delayed:** Repeated and/or prolonged exposures to low concentrations of vapors or aerosols may cause: sore throat, asthma, eye disease, kidney disorders, liver disorders, skin disorders and allergies.
- **4.3 Indication of any immediate medical attention and special treatment needed:** NOTE TO PHYSICIANS: Application of corticosteroid cream has been effective in treating skin irritation.

5 Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents: Foam, Fire-extinguishing powder, Carbon dioxide

5.2 Specific hazards arising from the substance or mixture: May generate ammonia gas. May generate toxic nitrogen oxide gases. Burning produces noxious and toxic fumes. Downwind personnel must be evacuated.

5.3 Advice for the firefighters

Protective equipment: Wear self-contained respiratory protective device, Wear fully protective suit

Additional information: Cool endangered receptacles with water fog or haze. Eliminate all ignition sources if safe to do so.

6 Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures: Use respiratory protective device against the effects of fumes/dust/aerosol. Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation. Keep away from ignition sources.

6.2 Environmental precautions: Do not allow to enter sewers/surface or ground water. Inform respective authorities in case of seepage into water course or sewage system. Prevent from spreading (e.g. by damming–in or oil barriers).

6.3 Methods and material for containment and cleaning up: Send for recovery or disposal in suitable receptacles. Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.

Revision Date 10.04.2017 Revision: 1

7 Handling and storage

7.1 Precautions for safe handling: Use only in well-ventilated areas. Store in cool, dry place in tightly closed receptacles (60-80°F recommended).

7.2 Conditions for safe storage, including any incompatibilities: Use only receptacles specifically permitted for this substance/product. Avoid storage near extreme heat, ignition sources or open flame.

Further Information about storage conditions: Keep container tightly sealed. Store in an area with adequate ventilation.

8 Exposure controls/personal protection

8.1 Control parameters

Exposure Limits: No data available for mixture itself.

8.2 Engineering controls Provide readily accessible eye wash stations and safety showers. Provide ventilation adequate to ensure concentrations are minimized.

8.3 Personal protective equipment

General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Do not inhale gases / fumes / aerosols. Avoid contact with the eyes and skin.

Respiratory protection: Not required under normal conditions of use. Use suitable respiratory protective device in case of insufficient ventilation. For spills, respiratory protection may be advisable. Use respiratory protection when grinding or cutting material.

Hand protection: Protective, impervious gloves. (Neoprene, Butyl-rubber, Nitrile rubber) The glove material has to be impermeable and resistant to the product / the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation.

Eye protection: Face shield with safety glasses or goggles underneath. Contact lenses should not be worn.

Skin and Body protection: Protective work clothing. Where potential exposure warrants, rubber or plastic boots and chemically resistant protective suit.

9 Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Appearance

Form: Paste Colour: Red Odour: Amine

Odour threshold: No data available

pH: Alkaline

Melting point/range: No data available Boiling point/range: >350 °F / >176 °C Flash point: >200 °F / >93 °C Evaporation rate: No data available Flammability (solid, gaseous): Not applicable Upper/lower flammability or explosive limit: Not applicable Vapor pressure: No data available Vapor density: No data available Relative Density at 20°C: 2.16 g/cm3

Solubility in / Miscibility with

Water: Not miscible or difficult to mix.

Partition coefficient (n-octanol/water):

Auto/Self-ignition temperature:

No data available

No data available

No data available

Viscosity Paste

Revision Date 10.04.2017 Revision: 1

10 Stability and reactivity

10.1 Reactivity

10.2 Chemical stability

Thermal decomposition / conditions to be avoided: No decomposition if used and stored according to specifications.

10.3 Possibility of hazardous reactions: Reacts with strong alkali. Exothermic polymerization. Reacts with strong acids and oxidizing agents. Reacts with catalysts.

10.4 Conditions to avoid: Avoid contact with strong oxidizing agents, excessive heat or flames.

10.5 Incompatible materials: Strong acids, bases and oxidizing agents.

10.6 Hazardous decomposition products: Nitric acid, Ammonia, Nitrogen oxides (NOx), Nitrogen oxide can react with water vapors to form corrosive nitric acid, Carbon monoxide, Carbon dioxide (CO2), Aldehydes, Flammable hydrocarbon fragments.

11 Toxicological information

11.1 Information on likely routes of exposure:

Skin contact: Harmful in contact with skin. Causes skin burns.

Eye contact: Causes eye burns.

Ingestion: Harmful if swallowed. If ingested, severe burns of the mouth and throat, as well as a danger of

perforation of the esophagus and the stomach.

Inhalation: Can cause severe eye, skin and respiratory tract burns.

11.2 Symptoms related to physical, chemical and toxicological characteristics: No data available.

11.3 Delayed and immediate effects as well as chronic effects from short and long-term exposure:

This product contains no listed carcinogens according to IARC, ACGIH, NTP and/or OSHA in concentrations of 0.1 percent or greater. May cause allergic skin reaction. This product may cause adverse reproductive effects. Eye disease, Skin disorders and Allergies.

11.4 Numerical measures of toxicity: No data is available for full mixture.

12 Ecological information

12.1 Aquatic toxicity: No data available on the product itself.

Toxicity to algae - Components

Benzene-1,3-dimethaneamine (MXDA) EC50 (72 h): 12 mg/l Species: Scenedesmus subspicatus

Toxicity to other organisms: No data available.

12.2 Persistence and degradability: No data available.

12.3 Bioaccumulative potential: No data available on the product itself.

12.4 Mobility in soil: No data available.

12.5 Other adverse effects: No further relevant information available.

13 Disposal considerations

13.1 Waste treatment methods

Waste from residue/unused product: This product should not be allowed to enter drains, water courses or the soil.

Dispose of this material in a safe manner and in accordance with federal, state and local regulations

Contaminated packaging: Disposal must be made in accordance with official federal, state and local regulations.

14 Transport information

DOT

UN number: UN3259

Proper Shipping Name: Amines, solid, corrosive, n.o.s., (Polyamidoamine, Aliphatic amine)

Hazard Class: 8
Packing Group: III
Labels(s): 8
Marine Pollutant: No

IATA

UN number: UN3259

Proper Shipping Name: Amines, solid, corrosive, n.o.s., (Polyamidoamine, Aliphatic amine)

Hazard Class: 8
Packing Group: |||

Revision Date 10.04.2017 Revision: 1

Labels(s): 8
Marine Pollutant: No

IMDG

UN number: UN3259

Proper Shipping Name: Amines, solid, corrosive, n.o.s., (Polyamidoamine, Aliphatic amine)

Hazard Class: 8
Packing Group: III
Labels(s): 8
Marine Pollutant: No

TDG

UN number: UN3259

Proper Shipping Name: Amines, solid, corrosive, n.o.s., (Polyamidoamine, Aliphatic amine)

Hazard Class: 8
Packing Group: III
Labels(s): 8
Marine Pollutant: No

15 Regulatory Information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Toxic Substance Control Act (TSCA) 12(b) Component(s): None.

Country	Regulatory list	Notification
USA	TSĈA	Included on Inventory.
EU	EINECS	Included on EINECS inventory or
		polymer substance, monomers
		included on EINECS inventory or
		no longer polymer.
Canada	DSL	Included on Inventory.
Australia	AICS	Included on Inventory.
Japan	ENCS	Included on Inventory.
South Korea	ECL	Included on Inventory.
China	SEPA	Included on Inventory.
Philippines	PICCS	Included on Inventory.

SARA

- ;	Section 355 (extremely hazardous substances):
	None of the ingredients is listed.
	Section 313 (Specific toxic chemical listings):
(Component(s) above 'de minimus' level: Phenol, 4,4'-(1-methylethylidene)bis-
_	TSCA (Toxic Substances Control Act):
	All the ingredients are listed.

Proposition 65 (California):

Chemicals known to cause cancer or reproductive toxicity: Phenol, 4.4'-(1-methylethylidene)bis-

15.2 Chemical Safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Abbreviation and acronyms:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labeling of Chemicals

Revision Date 10.04.2017 Revision: 1

ACGIH: American Conference of Governmental Industrial Hygienist. EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substance CAS: Chemical Abstracts Service (division of the American Chemical Society) HMIS: Hazardous Materials Identification System (USA) WHMIS: Workplace Hazardous Materials Information System (Canada)