

SCProbond™ SSiC

Sintered Silicon Carbide

- Sintered silicon carbide is produced from extremely fine, sub-micron, silicon carbide powder and non-oxide sintering additives. This material displays an extremely high corrosion resistance in acidic and basic media, and is maintained up to extremely high temperatures.
- Properties are outstanding among high-temperature ceramics, complemented by high thermal shock resistance, high thermal conductivity, high resistance to wear and a hardness close to that of diamond.
- Ideal for extremely demanding applications. For example, slip ring seals in chemical pumps, bearing bushes, high temperature burner nozzles, or as kiln furniture for very high application temperatures.

Markets that widely use this type of material include, but are not limited to:

- * Mining
- * Pulp and Paper
- * Chemical
- * Petrochemical
- * Power Generation

Applications Include:

- * Nozzles
- * Cyclones
- * Spigots
- * Impeller Rings
- * Apexes
- * Valves
- * Suction Pumps
- * Chutes
- * Autoclave Parts
- * Vessel and Pipe Linings
- * Bearing Seals
- * Dust Collectors
- * Cones

Physical Property	Units	Value
Composition	-	SiC
Grain Size	µm	4-10
Density	g/cc	3.15
Hardness (Knoop)	GPa	28.00
Modulus of Rupture	Mpa	380
Tensile Strength	MPa	250
Compressive Strength	MPa	3,900
Elastic Modulus	GPa	410
Coefficient of Thermal Expansion 20-1,000 °C	$1 \times 10^{-6} / ^\circ\text{C}$	4
Thermal Conductivity	W/mK	125
Poisson's Ratio	-	0.16



Silicon Carbide Products, LLC
361 Daniel Zenker Drive
Horseheads, New York 14845 USA
Telephone: +1-607-562-8599
Fax: +1-607-562-7585
Email: scp@scprobond.com

